

AY-K25

Mifare® Contactless Smartcard Reader



THIS NEW, RIGID, AND RELIABLE UNIT PROVIDES THE CAPABILITY TO READ MIFARE® SMARTCARD CONTACTLESS CARDS WITH ANY STANDARD ACCESS CONTROL SYSTEM. WITH 7 PROGRAMMABLE OUTPUT FORMATS, IT WILL FIT MOST EXISTING SYSTEM'S NEEDS AND READ THE INFORMATION REQUIRED.

THE AY-K25 IS FULLY-POTTED, SEALED AND MADE OF A RIGID, UV RESISTANT POLY-CARBONATE, WHICH MAKES IT HIGHLY SUITABLE FOR OUTDOOR USE. WITH A MAXIMUM RANGE OF 4 CM (1.57 IN.), IT IS A VERY SIMPLE, RELIABLE AND COST EFFECTIVE WAY TO UPGRADE YOUR SYSTEM TO THE SMARTCARD STANDARD.

GENERAL DESCRIPTION

The affordably priced AY-K25 reader is a contactless Serial ID Only reader that functions by reading Mifare® ID Format Protocol via a variety of 13.56 MHz cards and tags.

The adaptable AY-K25 is the answer for global companies seeking a uniform reader compatible with differing international mounting standards. Made of tough polycarbonate UV plastic and completely waterproof, the durable reader can withstand harsh weather conditions and tampering.

MAIN FEATURES

- Incorporates the ISO-14443A (Mifare®) ID Format Protocol
- Read range of up to 40 mm (1.57 in.)
- Designed under Rosslare's ISO 9001:2008 Certified Quality standards
- Multiple, programmable output formats including standard Wiegand 26-Bit

- Selectable LED control or buzzer control functions
- Made of tough polycarbonate plastic for improved performance in all weather conditions

PROFESSIONAL GRADE FEATURES

- Optical back tamper detection technology
- Bi-colored LED and LED control input
- Internal buzzer
- PC software and programming adapter (MD-08B) for easy configuration of the unit
- Weather-resistant

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	5–16 VDC, from a regulated power supply
■ Input Current	Standby: 49 mA @ 12 VDC Maximum: 67 mA @ 12 VDC
■ Tamper Output	Open collector, active low, max. sink current is 16 mA

OPERATIONAL SPECIFICATIONS

■ Inputs	Programmable LED control/buzzer control Input, N.O, Dry Contact
■ Indicators	Tri-colored LED indicators
■ Output Format	Programmable multi-format: Wiegand 26-Bit w/site code, Fixed 26-Bit, 32-Bit, 32-Bit Reversed, 34-Bit, 40-Bit, and Clock & Data
■ Built-In Proximity Reader	Max. read range: 40 mm (1.57 in.) Operating Frequency: 13.56 MHz Compatible Cards: Mifare® Compatible ISO-14443A

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Water resistant, suitable for outdoor use (IP65 rated)
■ Operating Temperature	-31°C to 63°C (-25°F to 145°F)
■ Operating Humidity	0 to 95% (non-condensing)

PHYSICAL SPECIFICATIONS

■ Dimensions (H x W x D)	80 x 40 x 13 mm (3.15 x 1.57 x 0.51 in.)
■ Weight	54 g (1.9 oz)

SYSTEM COMPONENTS

The AY-K25 is compatible with a variety of Rosslare's controllers, as well as with many third-party systems, and is compatible with Rosslare's AT-T511, AT-T521 & AT-T531 Ultralight (64 bytes), 1K and 4K Mifare® cards

PRODUCT WARRANTY

5-year Limited Product Warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

Visit our website: www.rosslaresecurity.com

Mifare® is a Trademark of NXP Semiconductors



ROSSLARE
SECURITY PRODUCTS
Experience The Difference