



FF756

UV / Dual IR flame detector in Eexd - IIC T6 flame proof housing

General

Dual infrared (IR²) and UV/IR² models have excellent response to flame while providing immunity to extraneous sources. New microprocessor technology makes the detectors independent of flame intensity enabling it to operate through smoke, a layer of oil, dust, or water vapour. A high and low sensitivity setting according to EN54-10 is provided.

Installer and maintenance friendly

The units can be wired as conventional 2 wire, 4-20 mA, or relay contacts (fire, fault and pre alarm) in latching or non-latching operation. Remote test inputs are available to activate self-test.

IP65, explosion & flameproof enclosures, and intrinsic safe models are available. A stainless steel adjustable bracket and weather shield is also available.

The units are tolerant to vibration, and wind does not affect the performance. The IR² unit has excellent tolerance to detector window contamination and can detect flame through glass windows.

A flame sensor test unit is available for accurate testing of the detectors.



Standard Features

- UV/Dual IR detector
- High specification units for critical applications
- Flame proof housing
- Low current consumption
- 2 Wire, 4 - 20 mA and relay operation
- Latching and non latching operation
- High / Low sensitivity setting
- Versatile mounting brackets
- Tolerance to detector window contamination
- Versatile, adjustable test torch available
- Remote self test facility
- Microprocessor controlled
- Immunity to false sources (arc welding, lightning and static)
- Conforms to EN54: Part 10



FF756

UV / Dual IR flame detector in Eexd - IIC T6 flame proof housing

Specifications

Supply voltage	14 - 28 V dc
Supply current	3/9, 4/8/14, 4-20, 8-20 mA
Relay contact ratings	1 A @ 30 V dc (resistive load)
Field of view	90° min. cone
Spectral response (IR)	1.0 to 2 microm
Operating temperature	-10°C to 55°C
Storage temperature	-20°C to 65°C
Relative humidity	95%; non-condensing
IP Rating	IP66 flame proof box
Weight	2 kg flame proof box

Ordering Information

Part No.	Description
FF756	UV / Dual IR flame detector in Eexd - IIC T6 flame proof housing

Reducing false alarms

Most IR flame sensors respond to 4.3 m light, emitted by hydrocarbon flames. By responding to 1.0 to 2.7 m light emitted by every fire, all flickering flames can be detected. Gas fires not visible to the naked eye e.g. hydrogen may also be detected.

The IR² detectors, responding to adjacent IR wavelengths, enable it to discriminate between flames and spurious sources of IR radiation.

The combination of filters and signal processing allows the sensor to be used without risk of false alarms in difficult situations characterised by factors such as flickering sunlight.

The combination of UV and IR² detection, plus signal processing allows the UV / IR² sensor to be used without risk of false alarms in difficult situations characterised factors such as flickering blackbody radiation or arc welding.



www.gesecurity.net